



◆ SPECIFICATION

Model NO.	LBM24HTC100B	LBM24AD100V	LBM24HTC130S	LBM24HTC130J	LBM24HTC200F	LBM24HTC200FS	LBM24HTC200FV	LBM24HTC200EP	LBM24AD300NA	LBM24AD400V
Video Output Mode	AHD/CVI/TVI/CVBS	AHD	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/CVI/TVI/CVBS	AHD/TVI	AHD
Camera										
Image Sensor	OV9732	OV9732	IMX225	S3130	F22	IMX323	OV2718	MN34227	AR0330	OV4689
DSP	HTC960E	NVP2431H	HTC960E	HTC960E	HTC1080E	FH8550D	HTC1080E	HTC1088	NVP2470H	NVP2475H
Image Resolution	720P	720P	960P / 960H	1080P / 960H	1080P	1080P	1080P / 960H	1080P / 960H	3MP / 960H	4MP
Effective Pixels	1280*720	1280*720	1280*960	1280*960	1920*1080	1920*1080	1920*1080	1920*1080	2048*1536	2560*1440
TV System	PAL/NTSC									
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s									
S/N Ratio	≥50dB									
Scanning System	Progressive Scan									
Lens										
Focus Length	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm	3.6mm
Focus Control	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
Pixels	2M Pixels	2M Pixels	2M Pixels	2M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	3M Pixels	5M Pixels
Auto Iris Support	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
Night Vision										
Infrared LED	14μ x 18PCS									
Infrared Distance	20M									
IR Status	Under 10 Lux by CDS									
IR Power On	CDS Auto Control									
Camera Features										
Day/Night	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
OSD Menu Language	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO	AUTO
Noise Reduction	DNR	3DNR	DNR	DNR	DNR	3DNR	DNR	3DNR	DNR	DNR
Picture Adjustment	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES
WDR	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES
OSD Support	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES
UTC	YES	NO	YES	YES	YES	YES	YES	YES	YES	YES
General										
Housing	Plastic, IP66									
Bracket	YES									
Dual Voltage	NO									
IR Cut Filter	YES									
Heater	NO									
Operation Temperature	-10℃ ~ +50℃ RH95% Max									
Storage Temperature	-20℃ ~ +60℃ RH95% Max									
Power Source	DC12V±10%, 500mA									
Dimension	160.8 (W) x 62 (H) x 62 (D) mm									
Weight	380g									